

TECHNICAL SHEET

BARI S3 WR HRO

ART. G-BARI S3 WR HRO SRC





EN ISO 20345:2011

UPPER

Water-repellent full-grain leather, with padded collar in hardwearing Cordura® fabric, Carbon leather side application and Hi-Vis heel insert

INNER LINING

WR Windtex® membrane, waterproof and breathable with windproof action and microclimate maintenance

TOE CAP

Steel, resistant to shocks up to 200J and compression up to 15Kn

ANTI-PERFORATION MIDSOLE

Stainless steel, resistant up to 1100N

FOOTBED

"Elisa", in antistatic and soft PU, ergonomic with shock absorbing cushion on the heel and lining in breathable textile; removable and washable

OUTSOLE

Double-density PU/Rubber, antistatic, Heat resistant up to 300°C (1 minute) and 150°C (30 min.) by sole contact, SRC slip resistant, oil and hydrocarbons resistant, shock absorbing in the heel

FIT

Mondopoint 10,5 - Regular

PACKAGING

100% recyclable PAP 20

WORKING ENVIRONMENT Outdoor. Road works, metallurgical and steel industry, construction, mining, foundries and stone quarrying, heavy industry

SIZES

EU: 40 – 47 / UK: 6,6 - 12

SAFETY CATEGORY

S3 WR HRO SRC

WEIGHT

850GR ½ pair size 42









Alba & N. s.r.l





